

# You've got 2.5 seconds

## NanoPhotometer® C40

### Cuvette Spectroscopy



#### Cuvette Capability

Compatible with most quartz, glass, and plastic cuvettes  
Linear up to 2.6 Abs



#### Full Scan

2.5 - 4 seconds per reading  
200 to 900 nm  
Resolution better than 1.8 nm



#### Regulatory Compliance, Certainty in Real Time and IQ/OQ Package

Optional CFR21 software provides password protected Role Based Access Control (RBAC), data integrity, electronic signatures and audit trail functionality

Impurity and air bubble recognition with Sample Control™ and Blank Control™

Compliant with international standards in regulated environments



WiFi

HotSpot

LAN



#### Endless Connectivity

Built-in File Server for data access from Windows and Mac computers  
Print to Airprint™ and HP Universal Driver compatible printers as well as DYMO Label printers  
REST API for LIMS integration



#### Battery Powered

Up to 8 hours battery operation



#### Flexible Unit Control and Ultimate Data Security

Computer (Windows & Mac)

Built-in touchscreen

Smartphone / Tablet (Android OS & iOS)

Proprietary NPOS immune to known threats

World's smallest footprint in its class: only 20 x 20 x 12 cm  
Ideal for nucleic acids, protein and samples in most organic solvents  
Upgradable to NanoVolume capability  
No reconditioning, no recalibration and no regular maintenance ever  
Stand-alone operation with built-in 7 inch glove compatible touch screen  
Universal data output: Excel and PDF | Multi Language User Interface | Barcode ready  
32 GB of onboard memory

# Technical Specifications

NanoVolume Performance		Optical Specifications	
Detection Range dsDNA	N60, NP80: 1 - 16,500 ng/μl N50: 5 - 7,500 ng/μl N120: 2 - 8,000 ng/μl	Wavelength Scan Range	C40, N60, NP80, N120: 200 - 900 nm N50: 200 - 650 nm
Detection Range BSA	N60, NP80: 0.03 - 478 mg/ml N50: 0.15 - 217 mg/ml N120: 0.06 - 230 mg/ml	Measure Time For Full Scan Range	C40, N50, N60, NP80: 2.5 - 4.0 sec N120: 1.7 - 2.5 sec per sample
Sample Volume	N50, N60, NP80: 0.3 - 2 μl N120: 2 - 3.5 μl	Wavelength Reproducibility	C40, N60, NP80, N120: ± 0.2 nm N50: ± 1 nm
Photometric Range (10 mm equivalent)	N60, NP80: 0.02 - 330 A N50: 0.1 - 150 A N120: 0.04 - 160 A	Wavelength Accuracy	C40, N60, NP80, N120: ± 0.75 nm N50: 1.5 nm
Path Length	N50, N60, NP80: 0.67 and 0.07 mm N120: 1 and 0.125 mm	Bandwidth	C40, N60, NP80: < 1.8 nm N50: 5 nm N120: < 2.5 nm
Dilution Factor	N50, N60, NP80: 15 and 140 N120: 10 and 80	Absorbance Reproducibility	N60, NP80: < 0.002 A (0.67 mm path) @ 280 nm N50: < 0.004 A (0.67 mm path) @ 280 nm N120: < 0.004 A (1 mm path) @ 280 nm
Vortex	N60, NP80: 2,800 rpm Tube size up to 2.0 ml	Absorbance Accuracy	< 1.75% @ 0.7 A @ 280 nm of the reading
<b>Cuvette Performance – NP80 &amp; C40</b>		Stray Light	N60, NP80: < 0.5% @ 240 nm using NaI N50: < 2% @ 240 nm using NaI N120: < 1% @ 240 nm using NaI
Detection Range dsDNA	0.1 - 130 ng/μl	Optical Arrangement	1 x 3648 CCD Array
Detection Range BSA	0.003 - 3.7 mg/ml	Lamp	Xenon flash lamp
Photometric Range	0 - 2.6 A	Lifetime	10 <sup>9</sup> flashes, up to 10 years
Center Height (Z-Height)	8.5 mm	<b>General Specifications</b>	
Cell Types	Outside dimension 12.5 x 12.5 mm	Main Body Size	200 x 200 x 120 mm
Heating	37 °C ± 0.5 °C	Weight	3.8 - 5.2 kg depending on configuration
<b>Processing Power &amp; Compatibility</b>		Operating Voltage	90 - 250 V, 50/60 Hz, 90 W, 18/19 VDC
Operating System	Linux based NPOS	Display	1024 x 600 pixels; glove compatible touchscreen
Onboard Processor	Intel Celeron dual core 2.4 GHz	Built-in Battery Pack	Optional rechargeable lithium ion battery: C40, N60, NP80: 95 Wh, 6.6 Ah, 8 h N120: 47.5 Wh, 3.3 Ah, 3 h Min. charging cycles: 800
Internal Data Storage	C40, N50, N60, NP80: 32 GB N120: 128 GB	Certification	CE, IEC 61010-1:2012 and EN 61326-1:2013
Software Compatibility	Windows 7, 8, 10 (32 & 64 bit) OS X, iOS Android OS	Battery Certification	IEC 62133 and UN38.3 transport test
		In & Output Ports	2x USB A, USB B, HDMI, Ethernet, WiFi
		Security	Slot for Kensington lock

## Reviews

“Great accuracy of measurements, easy usage, really nice interface. ”

Rating: 5.0 ★★★★★

Application Area: Determination of the concentration of proteins and nucleic acids solutions

"C40 NanoPhotometer is a **great tool** to measure macromolecule concentrations in microvolumes. It surpasses our previous nanodrop machine as it does not need calibration and has more functions. **Easy interface** is a great advantage and the new function of **enzyme kinetics** together with **vortex** makes this small and handy tool a **multitask help in our lab**. The wi-fi functions enables us to print spectra quickly. Measurements are **repeatable and accurate**. I would recommend the equipment every biochemistry lab."

Joanna Sliwiak

Organization: Institute of Bioorganic Chemistry, Polish Academy of Sciences, Poznan, Poland

“Excellent”

Rating: 5.0 ★★★★★

Application Area: Biotechnology

"Easy to use. Excellent **quality** and data is **very reliable**."

Vineeta Ranjan

Organization: Neobiotechnologies, Inc.